# Specification



## ZE1900V-640

**ZERES 5 Series:** Electric with Integrated Hydraulics



Clamping Force       kN       1900         US Tons       214         Mold Opening Stroke       mm       470         in.       18.5         Minimum Mold Height       mm       200         in.       7.87         Maximum Mold Height       mm       550         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55         US Tons       6	Clamping Unit		ZE1900 V
Mold Opening Stroke       mm       470         in.       18.5         Minimum Mold Height       mm       200         in.       7.87         Maximum Mold Height       mm       550         in.       21.65         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55	Clamping Force	kN	1900
in.       18.5         Minimum Mold Height       mm       200         in.       7.87         Maximum Mold Height       mm       550         in.       21.65         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22,44x22,44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55		US Tons	214
Minimum Mold Height       mm       200         in.       7.87         Maximum Mold Height       mm       550         in.       21.65         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55	Mold Opening Stroke	mm	470
in.       7.87         Maximum Mold Height       mm       550         in.       21.65         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55		in.	18.5
Maximum Mold Height       mm       550         in.       21.65         Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55	Minimum Mold Height	mm	200
Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55		in.	7.87
Maximum Daylight       mm       1020         in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55	Maximum Mold Height	mm	550
in.       40.16         Distance Between Tie-Bars (HXV)       mm       570x570         in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55		in.	21.65
Distance Between Tie-Bars (HXV)         mm         570x570           in.         22.44x22.44           Platen Dimensions (HXV)         mm         800x800           in.         31.5x31.5           Minimum Mold Size         mm         370x370           in.         14.57x14.57           Ejector Stroke         mm         130           in.         5.12           Ejector Force         kN         55	Maximum Daylight	mm	1020
in.       22.44x22.44         Platen Dimensions (HXV)       mm       800x800         in.       31.5x31.5         Minimum Mold Size       mm       370x370         in.       14.57x14.57         Ejector Stroke       mm       130         in.       5.12         Ejector Force       kN       55		in.	40.16
Platen Dimensions (HXV)         mm         800x800           in.         31.5x31.5           Minimum Mold Size         mm         370x370           in.         14.57x14.57           Ejector Stroke         mm         130           in.         5.12           Ejector Force         kN         55	Distance Between Tie-Bars (HXV)	mm	570x570
in.         31.5x31.5           Minimum Mold Size         mm         370x370           in.         14.57x14.57           Ejector Stroke         mm         130           in.         5.12           Ejector Force         kN         55		in.	22.44x22.44
Minimum Mold Size         mm         370x370           in.         14.57x14.57           Ejector Stroke         mm         130           in.         5.12           Ejector Force         kN         55	Platen Dimensions (HXV)	mm	800x800
in.         14.57x14.57           Ejector Stroke         mm         130           in.         5.12           Ejector Force         kN         55		in.	31.5x31.5
Ejector Stroke mm 130 in. 5.12 Ejector Force kN 55	Minimum Mold Size	mm	370x370
in. 5.12 Ejector Force kN 55		in.	14.57x14.57
Ejector Force kN 55	Ejector Stroke	mm	130
		in.	5.12
US Tons 6	Ejector Force	kN	55
		US Tons	6

## Specification



## ZE1900V-640

**ZERES 5 Series:** Electric with Integrated Hydraulics

Injection Unit		640		
Screw & Barrel Designation		А	В	С
Screw Diameter	mm	40	45	50
	in.	1.57	1.77	1.97
Screw L/D Ratio	L/D	22.5	20	18
Injection Volume (Theoretical)	cm3	252	319	394
	cu.in.	15.38	19.47	24.04
Injection Weight (PS)	g	229	290	358
	OZ.	8.08	10.23	12.63
Injection Pressure	MPa	253	200	162
	psi	36695	29008	23496
Holding Pressure	MPa	202	160	130
	psi	29298	23206	18855
Screw Speed	rpm	350	350	350
Plasticizing Rate (GPPS)	g/s	27	39	50
	oz./s	0.95	1.38	1.76
Nozzle Contact Force	kN	65	65	65
	US Tons	7	7	7
Injection Unit			640	
Injection Speed	mm/s		160	
	in./s		6.3	
Injection Rate (PS)	g/s	175	222	274
	oz./s	6.17	7.83	9.67
Injection Unit			640h	
Injection Speed	mm/s		250	
	in./s		9.84	
Injection Rate (PS)	g/s	274	347	428
	oz./s	9.67	12.24	15.10
Injection Unit			640hs	
Injection Speed	mm/s		350	
	in./s		13.78	
Injection Rate (PS)	g/s	384	486	600
	oz./s	13.55	17.14	21.16

## Specification




### ZE1900V-640

#### **ZERES 5 Series:** Electric with Integrated Hydraulics

Other		
Connection Power	kW/A	640:28/47
		640h:32/53
		640hs:49/82
Heating Power	kW	14.8
Machine Dimension	m	5.99x1.52x2.29
	in.	236x60x90
Machine Weight	t	7.9
	lbs.	17417
Hopper Capacity	I	25
	gal	7
Oil Pressure	MPa	17.5
	psi	2538
Oil Flow	l/min	79
	gal/min	21
Oil Tank	I	107
	gal	28

#### \*NOTE:

- 1. Machine dimensions and weights are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Absolute Haitian service department for machine specific information.
- 2. Power requirements are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Absolute Haitian service department for machine specific information.



# Fixed Platen

# Moving Platen



Absolute Haitian Corporation
33 Southgate St. Worcester, MA
T:+1 508-792-4305
www.absolutehaitian.com

Title: ZE/VEV 1900 Fixed & Moving Platens Drawing						
Machine Model: ZE/VEV 1900		Sheet: 1 of 1				
Machine Serial Number: Machine Tonnage:		Drawn By: Harry	Date: 1/9/2024			
				Chkd By:LEON XIE	Date: 1/9/2024	
Revision	Date:	Drawing #:		NOT TO SCALE	Size: 11 X 17 "B"	
Rev #: 1					Units: mm / [in]	
Rev #: 2					Material:	
Rev #: 3					Part:  Part:	
Rev #: 4					Part: Part:	
Rev #: 5					Part: Part:	


#### PLEASE READ


The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:


Customer Approval:
Authorized Signature

Notes:





- \*1 Power in Current and Power Cable are shown in the Main Power Supply Circuit
- \*2 To the mounting face of the fixed platen
- \*3 To the face of Hopper fixing platform
- \*4 To the top of the fixed platen
- \*5 Vibration dumping support





Absolute Haitian Corporation 33 Southgate St. Worcester, MA T:+1 508-792-4305 www.absolutehaitian.com

Title: ZE V 1900-640 Layout Drawing						
Machine Model: ZE V 1900-640 Machine Serial Number: Machine Tonnage:			Sheet: 1 of 1			
			Drawn By: Harry	Date: 3/22/2024		
				Chkd By:LEON XIE	Date: 3/22/2024	
Revision	Date:	Drawing #: Layout		NOT TO SCALE	<b>Size:</b> 11 X 17 "B"	
Rev #: 1					Units: mm / [in]	
Rev #: 2					Material:	
Rev #: 3					Part:  Part:	
Rev #: 4					Part: Part:	
Rev #: 5					Part: Part:	

PLEASE READ


The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.


Notes:

Customer:

Customer Approval:

Authorized Si







Absolute Haitian Corporation
33 Southgate St. Worcester, MA
T:+1 508-792-4305
www.absolutehaitian.com

Title: ZE V 1900 Robot Mounting Drawing						
Machine Model: ZE V 1900 Machine Serial Number: Machine Tonnage:		Sheet: 1 of 1				
		Drawn By: Harry	Date: 4/9/2024			
			Chkd By:LEON XIE	Date: 4/9/2024		
Revision	Date:	Drawing #: Robot Mounting	NOT TO SCALE	<b>Size</b> : 11 X 17 "B"		
Rev #: 1				Units: mm / [in]		
Rev #: 2				Material:		
Rev #: 3				Part: Part:		
Rev #: 4				Part: Part:		
Rev #: 5				Part: Part:		

#### PLEASE READ:

The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:

Customer Approval:
Authorized Signature

Notes: